

# Versatile, lightweight and efficient...

## NEW: nora<sup>®</sup> Lunatec combi 7



nora<sup>®</sup> Lunatec combi 7 is the consequent further development of the nora<sup>®</sup> Lunatec combi composite sheets. Two different materials are joined already during the manufacturing process and offer secure strength, *without any bonding*.

nora<sup>®</sup> Lunatec combi 7 consists of the proven qualities nora<sup>®</sup> Lunasoft SL and nora<sup>®</sup> Lunasoft SLW. With this combination, two high-quality, lightweight and soft EVA materials, which in practice are often used as constructive functional layers, are firmly combined.

The two materials nora<sup>®</sup> Lunasoft SL and nora<sup>®</sup> Lunasoft SLW must no longer be pasted together but can be processed in only **one single step**.

### Properties and product benefits:

- **Extremely lightweight, soft, and certified EVA material**  
ideal cushioning and shock-absorbing material for inserts and foot beddings
- **Permanently resilient cushioning layer and stabilising layer in one single product** thanks to the combination of Lunasoft SL and Lunasoft SLW
- **Efficient processing**  
thanks to less material usage and less grinding.
- **No bonding required and no displacement**  
of the different materials when processing.
- **High level of retention of volume** because the material is only compressed at the required places and no deep drawing is required.

### Areas of application:

nora<sup>®</sup> Lunatec combi 7 is the ideal basis for the efficient manufacture of inserts in only a few steps or a soft liner in only one step. In combination with other nora<sup>®</sup> Luna products, this material is the perfect basis for orthopaedic foot beddings.

### Product details:

#### nora<sup>®</sup> Lunatec combi 7

the vulcanised combination of:

#### nora<sup>®</sup> Lunasoft SLW

Density: approx. 0.20 g/cm<sup>3</sup>  
Hardness: approx. 30 Shore A  
Colour: 07 flesh colour  
Thickness: approx. 3 mm

**permanently resilient  
cushioning properties**

**Format:** approx.: 1150 x 800mm



#### nora<sup>®</sup> Lunasoft SL

Density: approx. 0.20 g/cm<sup>3</sup>  
Hardness: approx. 40 Shore A  
Colour: 19 stone grey  
Thickness: approx. 4mm

**stabilising properties**

**Total thickness:** approx. 7 mm

nora<sup>®</sup> Product novelty nora<sup>®</sup> Lunatec combi 7